



IP66 IK10 CLASS I CE

# ESCALADE LED

A modern, general purpose, hermetic, IP66 LED luminaire, providing direct illumination that can be suspended or surface mounted for maximum flexibility.

Ideal for lighting aisles, storage areas, warehouses and other industrial spaces.

# ESCALADE LED

## FEATURES & BENEFITS

- > Easy to install - Smooth adjustment of fastener spacing.
- > Wieland RST outlet - through-wiring on request
- > Optimum colour consistency - 3 step MacAdam chromaticity tolerance
- > Average rated LED life: >72,000hrs (L80/B10)

## PERFORMANCE


Light source	LED
LED output	7200 - 21600lm
Luminaire output	5350 - 19650lm
Beam angle	45°/65°/100°
CRI	84

## MATERIALS

Body	Aluminium
Finish	Grey
Diffuser	Clear tempered glass (45°/65°) Frosted tempered glass (100°)

## OPTIONS

- > Other RAL finishes
- > Brackets for wall mounting



81W, 4000K, 1160mm



600/1160/1720



64

64

LAMP	COLOUR TEMP	DELIVERED LUMENS	BEAM	LENGTH	SURFACE		SUSPENDED	
					STANDARD	DALI	STANDARD	DALI
42W	4000K	6510lm	45°	600mm	25600101	25600103	25600201	25600203
42W	4000K	6340lm	65°	600mm	25600301	25600303	25600401	25600403
42W	4000K	5350lm	100°	600mm	25600501	25600503	25600601	25600603
40W	4000K	6440lm	45°	1160mm	25600701	25600703	25600801	25600803
40W	4000K	6280lm	65°	1160mm	25600901	25600903	25601001	25601003
40W	4000K	5280lm	100°	1160mm	25601101	25601103	25601201	25601203
81W	4000K	13030lm	45°	1160mm	25601301	25601303	25601401	25601403
81W	4000K	12680lm	65°	1160mm	25601501	25601503	25601601	25601603
81W	4000K	10710lm	100°	1160mm	25601701	25601703	25601801	25601803
60W	4000K	9660lm	45°	1720mm	25601901	25601903	25602001	25602003
60W	4000K	9420lm	65°	1720mm	25602101	25602103	25602201	25602203
60W	4000K	7980lm	100°	1720mm	25602301	25602303	25602401	25602403
121W	4000K	19540lm	45°	1720mm	25602501	25602503	25602601	25602603
121W	4000K	19020lm	65°	1720mm	25602701	25602703	25602801	25602803
121W	4000K	16060lm	100°	1720mm	25602901	25602903	25603001	25603003